

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : RCS 5000 Acrylic Restoration Coatings System
Product code : RCS 5000 Series

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Fluid applied elastomeric roof coating designed to extend the life of a new and existing built-up asphalt, modified bitumen, asphalt shingles, single-ply, galvanized metal, concrete, and plywood roofs. Ideal for low slope roofs with positive drainage.
Use of the substance/mixture : For professional use only

1.3. Details of the supplier of the safety data sheet

Huntsman Building Solutions
3315 E. Division Street,
Arlington, TX 76011
Tel: 817-640-4900 , 888-224-153
sdsinfo@huntsmanbuilds.com

1.4. Emergency telephone number

Emergency number : CARECHEM (866) 928-0789

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin Sens. 1 H317
Carc. 2 H351

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS07

GHS08

Signal word (GHS-US) : Warning
Hazard statements (GHS-US) : H317 - May cause an allergic skin reaction
H351 - Suspected of causing cancer
Precautionary statements (GHS-US) : P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P261 - Avoid breathing mist, spray, vapours, fume, gas, dust
P272 - Contaminated work clothing must not be allowed out of the workplace
P280 - Wear eye protection, protective clothing, protective gloves
P302+P352 - If on skin: Wash with plenty of water
P308+P313 - If exposed or concerned: Get medical advice/attention
P321 - Specific treatment (see ... on this label)
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
P362+P364 - Take off contaminated clothing and wash it before reuse
P405 - Store locked up
P501 - Dispose of contents/container to comply with applicable local, national and international regulation.

2.3. Other hazards

other hazards which do not result in classification : Spilled material may present a slipping hazard. Spills may cause collapse or fall.

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Titanium dioxide	(CAS No) 13463-67-7	<10	Carc. 2, H351
Pentapotassium triphosphate	(CAS No) 13845-36-8	<1	Acute Tox. 4 (Oral), H302
Ammonia	(CAS No) 7664-41-7	<1	Flam. Gas 2, H221 Compressed gas, H280 Acute Tox. 3 (Inhalation:gas), H331 Skin Corr. 1B, H314 Eye Dam. 1, H318
3(2H)-Isothiazolone, 4,5-dichloro-2-octyl-	(CAS No) 64359-81-5	<0.25	Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317
Benzophenone	(CAS No) 119-61-9	<0.15	Carc. 2, H351

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: In all cases of doubt, or when symptoms persist, seek medical attention.
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get immediate medical advice/attention.
First-aid measures after skin contact	: Remove contaminated clothing and shoes. Wash hands with water and soap. Seek medical attention if irritation develops.
First-aid measures after eye contact	: In case of contact with eyes, rinse immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart. Subsequently consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately get medical attention.
First-aid measures after ingestion	: If swallowed, rinse mouth with water (only if the person is conscious). Immediately call a POISON CENTER or doctor/ physician. Give water to drink if victim completely conscious/alert. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: Inhalation of mist or aerosol may cause irritation to nose and throat . In case of repeated or prolonged exposure : Lungs irritation. Dizziness, headaches, nausea. Suspected of causing cancer if inhaled.
Symptoms/injuries after skin contact	: May cause an allergic skin reaction.
Symptoms/injuries after eye contact	: May cause eye irritation. symptoms may include stinging, tearing, redness, swelling and blurred vision.
Symptoms/injuries after ingestion	: Abdominal pain, nausea. Vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: carbon dioxide (CO2), water, dry chemical powder. Foam.
Unsuitable extinguishing media	: None known.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Firefighting instructions	: Exercise caution when fighting any chemical fire.
Protective equipment for firefighters	: Wear proper protective equipment. Wear a self contained breathing apparatus.
Other information	: Prevent entry to sewers and public waters. Material can splatter above 100° C (212° F). Dried product can burn.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Ensure adequate ventilation. The vapour is heavier than air; beware of pits and confined spaces. Spilled material may present a slipping hazard. Stop leak if safe to do so. No action shall be taken involving any personal risk or without suitable training.

6.1.1. For non-emergency personnel

Protective equipment : Wear suitable protective clothing. Refer to section 8.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.
Emergency procedures : Evacuate unnecessary personnel.

6.2. Environmental precautions

Do not discharge into drains or the environment. Relevant water authorities should be notified of any large spillage to water course or drain.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Wear proper protective equipment. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Collect all waste in suitable and labelled containers and dispose according to local legislation. Avoid static electricity discharges. Store away from other materials. Dispose of contents/container to comply with applicable local, national and international regulations.

6.4. Reference to other sections

For further information refer to section 8 : Exposure-controls/personal protection. For disposal of residues refer to section 13 : Disposal considerations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Use only in well-ventilated areas. Avoid all eye and skin contact and do not breathe vapour and mist. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container closed when not in use. Take precautionary measures against static discharge. Ensure adequate ventilation.
Hygiene measures : Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practices. Wash exposed skin thoroughly with soap and water after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Provide adequate ventilation. A washing facility/water for eye and skin cleaning purposes should be present.
Storage conditions : Keep out of reach of children. Keep container tightly closed in a cool place. Keep only in the original container in a cool, well-ventilated place away from highly flammable substances. Store away from direct sunlight or other heat sources. Avoid Freezing. PROTECT FROM FREEZING DURING SHIPMENT AND STORAGE.
Do not store material at temperatures below 50 °F (10 °C).
Incompatible materials : Strong oxidizing agents. Acids. Base.
Storage temperature : The minimum recommended storage temperature for this material is between 55 °F (13 °C) and 90 °F (32 °C). Keep from freezing, material may coagulate

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Titanium dioxide (13463-67-7)		
USA ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust)
Ammonia (7664-41-7)		
USA ACGIH	ACGIH TWA (ppm)	25 ppm
USA ACGIH	ACGIH STEL (ppm)	35 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	35 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	50 ppm

8.2. Exposure controls

Appropriate engineering controls : Provide adequate ventilation. Provide local exhaust or general room ventilation. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Personal protective equipment : Insufficient ventilation: wear respiratory protection. Protective goggles. Gloves. Protective clothing. For certain operations, additional Personal Protection Equipment (PPE) may be required.



Hand protection : Wear protective gloves. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Eye protection : Eye protection, including both chemical splash goggles and face shield, must be worn when possibility exists for eye contact due to spraying liquid or airborne particles. Contact lenses should not be worn.

Skin and body protection : Long sleeved protective clothing. Personal protective clothing should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling.

Respiratory protection : An approved organic vapour respirator/supplied air or self-contained breathing apparatus must be used when vapour concentration exceeds applicable exposure limits. Use an approved air purifying respirator equipped with an ammonia/methylamine cartridge. Respirators should be used in accordance with OSHA requirements (29 CFR 1910.134).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: White or colors
Odour	: Slight odour
Odour threshold	: No data available
pH	: 8.5 - 9.5
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 100 °C (212 °F)
Flash point	: < 96 °C (<205 °F)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: Heavier than air
Relative density	: No data available
Density	: 1.44 Specific Gravity
Solubility	: soluble in water. Water: Soluble
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content : 20.1 g/l (0.17 lb/gal)

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable at normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Avoid Freezing. Heat, open flame, sparks, hot surfaces, ignition sources, elevated temperature .

Avoid exposure to temperatures above 150 °F (65.6 °C)

May emit toxic materials when heated to 350° F (177 °C) or above.

10.5. Incompatible materials

Strong oxidizing agents. Acids. Base.

10.6. Hazardous decomposition products

Hazardous combustion products are Carbon dioxide, carbon monoxide, smoke, fumes, unburned hydrocarbons and oxides of sulfur, phosphorus, zinc and/or nitrogen.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Benzophenone (119-61-9)	
LD50 oral rat	> 10 g/kg
LD50 dermal rabbit	3535 mg/kg
ATE US (dermal)	3535.00000000 mg/kg bodyweight

Pentapotassium triphosphate (13845-36-8)	
LD50 oral rat	2000 mg/kg
ATE US (oral)	2000.00000000 mg/kg bodyweight

Titanium dioxide (13463-67-7)	
LD50 oral rat	> 10000 mg/kg

Ammonia (7664-41-7)	
LD50 oral rat	350 mg/kg
LC50 inhalation rat (ppm)	2000 ppm/4h
ATE US (oral)	350.00000000 mg/kg bodyweight
ATE US (gases)	2000.00000000 ppmv/4h

Skin corrosion/irritation : Not classified
pH: 8.5 - 9.5

Serious eye damage/irritation : Not classified
pH: 8.5 - 9.5

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Suspected of causing cancer.

Benzophenone (119-61-9)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity

Titanium dioxide (13463-67-7)	
IARC group	2B - Possibly carcinogenic to humans

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: Inhalation of mist or aerosol may cause irritation to nose and throat . In case of repeated or prolonged exposure : Lungs irritation. Dizziness, headaches, nausea. Suspected of causing cancer if inhaled.
Symptoms/injuries after skin contact	: May cause an allergic skin reaction.
Symptoms/injuries after eye contact	: May cause eye irritation. symptoms may include stinging, tearing, redness, swelling and blurred vision.
Symptoms/injuries after ingestion	: Abdominal pain, nausea. Vomiting.

SECTION 12: Ecological information

12.1. Toxicity

Benzophenone (119-61-9)	
LC50 fishes 1	13.2 - 15.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
Ammonia (7664-41-7)	
LC50 fishes 1	0.44 mg/l (Exposure time: 96 h - Species: Cyprinus carpio)
EC50 Daphnia 1	25.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	0.26 - 4.6 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Benzophenone (119-61-9)	
BCF fish 1	3.4 - 9.2
Log Pow	3.58
Ammonia (7664-41-7)	
Log Pow	-1.14 (at 25 °C)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other adverse effects	: Prevent entry to sewers and public waters.
Effect on ozone layer	: No additional information available
Effect on the global warming	: No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations	: Dispose of contents/container to comply with applicable local, national and international regulations. Consult the appropriate authorities about waste disposal.
Additional information	: Do not re-use empty containers. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose containers to flames, sparks, heat, or other potential ignition sources.
Ecology - waste materials	: Avoid release to the environment. Do not allow into drains or water courses.

SECTION 14: Transport information

In accordance with DOT
Not regulated for transport

Additional information

Other information	: No supplementary information available.
-------------------	---

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

Benzophenone (119-61-9)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
Ammonia (7664-41-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on the United States SARA Section 302	
Listed on United States SARA Section 313	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	100 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	500
SARA Section 313 - Emission Reporting	1.0 % (includes anhydrous Ammonia and aqueous Ammonia from water dissociable Ammonium salts and other sources, 10% of total aqueous Ammonia is reportable under this listing)

15.2. International regulations

CANADA

Titanium dioxide (13463-67-7)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
Ammonia (7664-41-7)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class A - Compressed Gas Class B Division 1 - Flammable Gas Class D Division 1 Subdivision A - Very toxic material causing immediate and serious toxic effects Class E - Corrosive Material

EU-Regulations

Ammonia (7664-41-7)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	

Classification according to Regulation (EC) No. 1272/2008 [CLP]

No additional information available

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

No additional information available

15.2.2. National regulations

Ammonia (7664-41-7)	
Listed on the AICS (Australian Inventory of Chemical Substances)	
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)	
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory	
Listed on the Korean ECL (Existing Chemicals List)	
Listed on NZIoC (New Zealand Inventory of Chemicals)	
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)	
Japanese Poisonous and Deleterious Substances Control Law	
Listed on the Canadian IDL (Ingredient Disclosure List)	

15.3. US State regulations

Benzophenone (119-61-9)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes				

Titanium dioxide (13463-67-7)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes				

SECTION 16: Other information

Indication of changes : 3. Composition/information on ingredients. 2.1. Classification of the substance or mixture, according to the federal final rule of hazard communication revised on 2012 (HazCom 2012).

Revision date : 11/5/2014 12:00:00 AM

Sources of Key data : SDS - Safety Data Sheet.

Other information : None.

Full text of H-phrases: see section 16:

Acute Tox. 3 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Carc. 2	Carcinogenicity, Category 2
Compressed gas	Gases under pressure : Compressed gas
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Gas 2	Flammable gases, Category 2
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Sens. 1	Sensitisation — Skin, category 1
H221	Flammable gas
H280	Contains gas under pressure; may explode if heated
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H331	Toxic if inhaled
H351	Suspected of causing cancer

SDS US (GHS HazCom 2012)

WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY HUNTSMAN BUILDING SOLUTIONS. HEREUNDER ARE GIVEN GRATIS AND HUNTSMAN BUILDING SOLUTIONS ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK. HUNTSMAN BUILDING SOLUTIONS WILL NOT MAKE ITS PRODUCTS AVAILABLE TO CUSTOMERS FOR USE IN THE MANUFACTURE OF MEDICAL DEVICES WHICH ARE INTENDED FOR PERMANENT IMPLANTATION IN THE HUMAN BODY OR IN PERMANENT CONTACT WITH INTERNAL BODILY TISSUES OR FLUIDS.